

## J-ANCHOR BOLTS **DIMENSIONAL INFORMATION** D D L C T WT. PER C Α 1/2" 3/8"-16 8" 1" 3" 25 3/8"-16 1/2" 1" 3" 10" 30 3/8"-1612" 1/2" 1" 3" 35 14" 3/8"-16 1/2" 1" 3" 40 1/2"-13 4" 8" 5/8" 1 1/4" 46 1/2"-13 5/8" 1 1/4" 4" 55 10 1/2"-13 1 1/4" 12" 5/8" 4" 64 4" 1/2"-13 5/8" 1 1/4" 16" 81 1/2"-13 5/8" 1 1/4" 18" 4" 90 3/4" 1 1/4" 5/8"-11 8" 4" 74 3/4" 1/4" 5/8"-1110" 4" 88 5/8"-11 12" 3/4" 1/4" 4" 102 5/8"-11 3/4" 1 1/4" 4" 115 14" 3/4" 1 1/4" 5/8"-11 4" 18" 143 3/4" 1 1/4" 5/8"-11 24" 4" 185 1 1/2" 3/4"-108" 1 1/8" 5" 118 3/4"-101 1/8" 1/2" 5" 10" 139 3/4"-10 1/2" 12" 1 1/8" 5" 160 3/4"-10 1 1/8" 1/2" 14" 5" 180 3/4"-10 1/2" 1 1/8" 5" 18" 220 3/4"-1024" 1 1/8" 1 1/2" 5" 285 10" 2 1/8" 3 1/4" 6" 1"-8 300 3 1/4" 1"-8 12" 2 1/8" 6" 338 3 1/4" 1"-8 18" 2 1/8" 6" 451

## **NOT ALL SIZES ARE STOCKED AT ALL TIMES**

- AVAILABLE IN HOT DIP GALVANIZED
- PLAIN, ZINC CLEAR, 304SS & 316SS UPON SPECIAL ORDER AT CURRENT MARKET PRICE ITEMS ARE PITCH BODY UNDERSIZED WITH ROLLED THREADS

2 1/8"

COMMERCIAL NUT FIT \*\* NOT UNC-2A FIT \*\*

24"

USA DOMESTIC MANUFACTURE

1"-8

SOLD BULK NO NUTS UNLESS SPECIFCALLY QUOTED OTHERWISE

DIAMETERS 1/2"-13 THRU 5/8"-11 GENERALLY MADE FROM COLD DRAWN 1006-1018 COIL STEEL DIAMETERS 3/4"-10 AND UP GENERALLY MADE FROM ASTM F1554 GR 55 S1 HOT ROLL ROUNDS HOT DIP GALVANIZED PER ASTM A153

ZINC PLATING IS PER ASTM F1941 TYPE V, CLASS SC., 0002 MIN THICKNESS 304SS PER ASTM A193
B8 CLASS 1 GENERALLY WHEN MATERIAL AVAILABLE 316SS PER ASTM A193 B8M CLASS 1 GENERALLY WHEN MATERIAL AVAILABLE

3 ¼"

6"

563