

## Exterior Nails

### Roofing Nail — Annular Ring Shank

#### Features:

- Large, flat head provides extra bearing surface to firmly secure roofing material
- Annular ring shank increases withdrawal resistance to provide a secure attachment to wood members and plywood roof decks
- Longer lengths ideal for installing curved Spanish roof tiles and thicker slate

#### Installation Tips:

- For slate roofs, determine the correct nail length by doubling the slate thickness and adding one inch



#### Type 304 Stainless Steel


Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	25 lb. Bucket Model No.
40d	5	8	0.162	½	28	S40ATNB*

\*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

### Specialty Nail — Fencing Staples

#### Type 304 Stainless Steel

Length (in.)	Screw Size/ Nail Gauge	Count per lb. (approx.)	Package Size	Model No.
1¼	13	202	1 lb.	S13125FS1
1¼	13	202	5 lb.	S13125FS5
1¼	13	202	25 lb.	S13125FSB




### Specialty Nail — Hog Rings — Hill Pattern

#### Features:

- #3 pre-bent

#### Type 304 Stainless Steel

Gauge	Width Open (in.)	Width Across (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
13	0.812	1.57	204	S13075HR1	S13075HR5	S13075HRB
14	0.280	0.75	540	S14075HR1	—	S14075HRB



These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.