Composite Decking Screws

Fascia-Fastening Solution[™]

PVC and Composite Fascia Applications

The Simpson Strong-Tie Fascia-Fastening Solution consists of the counterbore bit and fascia screw, and is specially designed to securely fasten composite and PVC fascia while providing superior corrosion resistance. The Fascia Fastening Solution allows for the expansion and contraction of installed fascia boards and thus prevents failures as a result of exposure to environmental conditions.

Fascia Screw

Screws


- Type 316 stainless steel provides severe-level corrosion resistance
- · Additional space around the shank of the fascia screw allows for the expansion and contraction of the fascia board
- · Low-profile pancake head resists pullover
- For use with 1/2"-3/4"-thick fascia boards

Counterbore Bit (sold separately)

- · Crucial for proper installation of fascia boards
- Creates pilot hole for clean installation
- · Creates a counterbore to allow a flush finish of the fascia screw head

Note: Refer to decking manufacturers' facia board installation guide for minimum spacing requirements.

For more information regarding driver bits for Simpson Strong-Tie fasteners, see p. 129.




· Available in 12 colors to match major

manufacturers' fascia material

• Approved for attachment of Trex®

Fascia Boards

· Bores space larger than screw shank to allow for fascia board expansion and contraction



Type 316, Stainless-Steel Painted Head

| Size x Length (in.) | Head Color | Head Diameter (in.) | Point Type | Drive Type | Model No. | Quantity |
|------------------------|------------|------------------------|------------|------------|----------------|----------|
| #8 x 1¾ | Brown 01 | 0.400 | Type-17 | T20 | T08175FS75BR01 | 75 |
| #8 x 1¾ | Brown 05 | 0.400 | Type-17 | T20 | T08175FS75BR05 | 75 |
| #8 x 1¾ | Gray | 0.400 | Type-17 | T20 | T08175FS75GR | 75 |
| #8 x 1¾ | Gray 01 | 0.400 | Type-17 | T20 | T08175FS75GR01 | 75 |
| #8 x 1¾ | Gray 04 | 0.400 | Type-17 | T20 | T08175FS75GR04 | 75 |
| #8 x 1¾ | Red | 0.400 | Type-17 | T20 | T08175FS75RD | 75 |
| #8 x 1¾ | Red 01 | 0.400 | Type-17 | T20 | T08175FS75RD01 | 75 |
| #8 x 1¾ | Tan | 0.400 | Type-17 | T20 | T08175FS75TN | 75 |
| #8 x 1¾ | Tan 01 | 0.400 | Type-17 | T20 | T08175FS75TN01 | 75 |
| #8 x 1¾ | Tan 02 | 0.400 | Type-17 | T20 | T08175FS75TN02 | 75 |
| #8 x 1¾ | Tan 03 | 0.400 | Type-17 | T20 | T08175FS75TN03 | 75 |
| #8 x 1¾ | White 01 | 0.400 | Type-17 | T20 | T08175FS75WH01 | 75 |



Fascia Counterbore Rit

| Arbor Size | Bore Diameter (in.) | Counterbore Diameter (in.) | Model No. | Quantity | | | | |
|------------|------------------------|-------------------------------|--------------|----------|--|--|--|--|
| 1⁄4" | 0.25 | 0.41 | FSBIT | 1 | | | | |